

INSTALLATION INSTRUCTIONS

FOR ANILLO APOLLONIA PENDANT ITEM 192970

Meyda
CUSTOM LIGHTING

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- A. CANOPY ASSEMBLY W/ DRIVER
- B. 72"W LED RING
- C. HUB
- D. AIRCRAFT CABLE (QTY 3)

Caution: Be sure power is off at the main breaker box prior to installation. Do Not turn power on until entire installation has been completed. Read all instructions in their entirety before beginning installation.

1. Carefully unpack all components and make certain that everything is accounted for.
2. Remove Acorn and Hex Nuts from Canopy to release Mounting Plate.
3. Affix Mounting Plate to Structure ensuring that connection is suitable for minimum 60lbs and that electrical supply wires remain accessible.
4. Make electrical connection from structure supply wires to Driver input wires following all local codes and procedures.
5. Slide Canopy with Driver over Studs on Mounting Plate and secure using Hex and Acorn Nuts.
6. Unravel preattached Aircraft Cable from Canopy and run to Hub. Be sure to attach Cable marked as Positive to Gripper marked as Positive. Do the same with Cable marked as Negative.
7. Set desired Cable length by loosening Nut at Top of Gripper and feeding Cable through. Push loosened Nut in and pull Cable to release. Once Cable length has been set, tighten Gripper Nuts. Excess Cable can be cut.
8. Attach Aircraft Cables to Grippers on bottom of Hub.
9. Run Cables to LED Ring ensuring to connect Positively labeled Gripper on Hub to Positively labeled Gripper on Ring. Do the same for Negative.
10. Set Cables to desired length using the aforementioned method. Minimum distance between LED Ring and Hub is 26".
11. Power on and ENJOY!!!

