FOR ITEM 138539



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL

INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- 1. CROSSBAR WITH STUDS AND ACCESS PANEL
- 2. REMOVABLE BOTTOM

Caution:

Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is on hand.
- 2. Unscrew the Brass Balls on the bottom of the Canopy to release the Crossbar.
- 3. Using Cutomer Supplied Harware, affix the Crossbar directly to the J-BOX ensuring the connection is suitable for 30 lbs and that electrical supply wires remain accessible.
- 4. Unscrew the bottom of the Shade using philips head screw driver and set aside until Bulbs are installed.
- 5. Lift the Fixture up to the ceiling and secure on the Crossbar using the Brass Balls from earlier.
- 6. Unscrew the Cap on the Canopy to remove the Wire Access Panel.
- 7. Following all local codes and procedures make electrical connections from supply wires to fixture lead wres.
- 8. Put the Wire Access Panel back on with the wires stuffed inside of the Canopy.
- 9. Install 5X 60WATT E26 A19 Bulbs (not included) into sockets.
- 10. Screw Removable Bottom back onto fixture.
- 11. Power on and ENJOY!!!

