INSTALLATION INSTRUCTIONS

FOR ITEM 141167 Smythe Craftsman Flushmount



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

Caution:

Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is accounted for.
- 2. Move Mica Panels from bottom of Shade to gain access to Fixture interior.
- 3. Remove Brass Balls from Canopy to release Crossbar.
- 4. Affix Crossbar to Junction Box ensuring that connection is suitable to hold a minimum of 15lbs and that Electrical Supply Wires remain accessible.
- 5. Following all Local Codes and Procedures, make electrical connection from Lead Wires to Supply Wires.
- 6. Lift Fixture up to ceiling allowing Crossbar Studs to pass through Canopy. Secure with Brass Balls.
- 7. Install 4-E26 60Watt Bulbs(not included) into Sockets.
- 8. Replace Mica Panels in bottom of Shade.
- 9. Power on and ENJOY!!!



