## INSTALLATION INSTRUCTIONS

FOR ITEM 143343 Bungalow White Alabaster Swirl 2 LT Vanity Light



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.\*

**Caution**: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

## FIXTURE COMPONENTS

- 1. 2 LIGHT HARDWARE
- 2. GLASS SHADE (QTY 2)

## Caution:

## Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is accounted for.
- 2. Loosen Set Screw at bottom of Hardware Back Plate allowing Back Plate to slide freely. Carefully slide Back Plate forward allowing access to Universal Crossbar.
- 3. Following all Local Codes and Procedures, make electrical connection from Hardware Lead Wires to Supply Wires.
- 4. Using Customer Supplied Fasteners, attach Universal Crossbar to Junction Box ensuring connection is suitable to hold a minimum of 5 lbs.
- 5. Slide Back Plate to wall and secure by tightening Set Screw.
- 6. Slide Glass Shades over Sockets and secure with provided Square Plate, Cork Ring, then thread Uno Ring onto Socket. It may be necessary to loosen Set Screws on Shade fitter to allow Shade to fully engage Fitter. Once Shade is fully seated into Fitter, tighten Set Screws finger tight. DO NOT OVETIGHTEN.
- 7. Install 2 Medium Base 60Watt Bulbs(not included) into Sockets.
- 8. Power on and ENJOY!!!

