

# INSTALLATION INSTRUCTIONS

FOR ITEM 145273 CHAVES OBLONG PENDANT

*Meyda*  
CUSTOM LIGHTING

**CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE.** We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.\*

**Caution:** Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

## FIXTURE COMPONENTS

1. 20" L STAINED GLASS SHADE
2. MISSION 2 LT PENDANT HARDWARE

**Caution: Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.**

1. Carefully unpack all components and make certain that everything is accounted for.
2. Unscrew Acorn Nuts from bottom of Canopy to release Universal Crossbar with Studs.
3. Attach Universal Crossbar to J-Box with customer supplied hardware ensuring that connection is suitable for from minimum 15lbs and that Line Wires remain accessible.
4. Unscrew Hex Nut and remove it and Spider Washer from Threaded Rod at top of Canopy.
5. Remove Canopy, Square Check Ring, Square Rod, 2nd Square Check Ring, and 1 Rubber Washer from Pendant Hardware.
6. Slide Shade over Threaded Rod and allow to rest on top of Rubber Washer at top of Light Cluster.
7. Reassemble Hardware by returning Rubber Washer, then Square Check Ring, Square Rod, 2nd Square Check Ring, and Canopy.
8. Return Spider Washer and Screw Hex Nut back onto exposed Threaded Rod at top of Canopy until tight.
9. Make electrical connection from Fixture Lead Wires to Structure Line Wires following all Local Codes and Procedures.
10. Slide Canopy over Studs on Universal Crossbar and Secure with Acorn Nuts.
11. Install 2 Medium 60 Watt Bulbs(not included).
12. Power on and ENJOY!!!

