INSTALLATION INSTRUCTIONS

FOR ITEM 149667 Harmony 2 Light Pot Rack



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- 1. CANOPY ASSEMBLY
- 2 48" CHAIN (QTY 2)
- 3. HUB W/DOWN LIGHTS
- 4. ARM (QTY 4)
- 5. POT RACK RING
- 6. POT HOOK (QTY 10)

Caution:

Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box. Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is accounted for.
- 2. Remove Nuts from Canopy Assembly to release Mounting Bar. Reserve Nuts for later use.
- 3. Using Customer Supplied Hardware, affix Mounting Bar to ceiling ensuring connection is suitable to hold a minimum of 50lbs. and that Electrical Supply Wires remain accessible.
- 4. Attach desired length of Chain to Loops on Hub.
- 5. Weave Lead Wires from top of Hub through every 5th Link of Chain.
- 6. Attach loose ends of Chain to Loops on Canopy and feed Lead Wires through Canopy Wireways.
- 7. Following All Local Codes and Procedures, make connection from Lead Wires to Supply Wires.
- 8. Lift Canopy up to ceiling allowing Mounting Bar Studs to pass through. Secure with reserved Nuts.
- 9. Hang Arms from Hub Loops with Hooks facing toward center.
- 10. Hang Pot Rack Ring from loose ends of Arms.
- 11. Slide Pot Hooks onto Pot Rack Ring.
- 12. Install 2-E26 60Watt Bulbs(not included) into Sockets.
- 13. Power on and ENJOY!!!

