## INSTALLATION INSTRUCTIONS

FOR ITEM 152825



## CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL

**INJURY OR DEATH AND PROPERTY DAMAGE.** We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.\*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

## FIXTURE COMPONENTS

- CROSSBAR W/STUDS
- 2. WIRE ACCESS PANEL
- 3. SHADES

## Caution:

Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- Carefully unpack all components and make certain that everything is on hand.
- Unscrew Brass Balls on the bottom of the Canopy to remove the Crossbar.
- 3. Using Customer supplied hardware, affix the crossbar directly to the J-box ensuring connection is suitable for a minimum of 15 lbs. and that electrical supply wires remain accessible.
- 4. Lift the Fixture up to ceiling, reattaching to the Crossbar using the Brass Balls from prior.
- Unscrew the Cap at the bottom of the Canopy to open the Wire Access Panel.
- Following all local codes and procedures, make electrical wire connections from the Supply wires to the Fixture lead wires and then push the wires back up through the Access Panel.
- 7. Reconnect the Wire Access Panel using the Cap from before.
- 8. Unscrew ring on each Socket, put each shade on and screw the ring back in place to secure the Shades.
- 9. Install 3x 40W E26 A19 Bulbs (not included) into sockets.
- 10. Power on and ENJOY!!!

