

INSTALLATION INSTRUCTIONS

FOR ITEM 153386 CILINDRO CAMPBELL FLUSHMOUNT

Meyda
CUSTOM LIGHTING

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

1. FLUSHMOUNT BODY
2. WHITE ACRYLIC DIFFUSER

Caution: Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

1. Carefully unpack all components and make certain that everything is accounted for.
2. Twist Acrylic Diffuser counter-clockwise to disengage and remove it.
3. Unscrew Brass Balls from roof inside Flushmount Body to release Universal Crossbar with Studs. Reserve Brass Balls for later use.
4. Using Hardware supplied with Junction Box, attach Universal Crossbar to Box with Studs facing down and ensuring that Electrical Supply Wires remain accessible.
5. Following all Local Codes and Procedures, make Electrical Connection from Fixture Lead Wires to Supply Wires.
6. Raise Flushmount Body to ceiling allowing Crossbar Studs to protrude through. Secure using Brass Balls. Top of Flushmount Body should be flush to ceiling.
7. Install 3 Medium Base 20Watt LED Bulbs(not included) into Sockets.
8. Reinstall Acrylic Diffuser by inserting top tabs into notches and twisting clockwise to secure.
9. Power on and ENJOY!!!

