INSTALLATION INSTRUCTIONS

FOR ITEM 160194



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL

INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- 1. CANOPY W/ LIGHT CLUSTER
- 2. FRAME

Caution:

Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is on hand.
- 2. Remove Brass Balls from bottom of Canopy to release Crossbar with Bolts. Keep Brass Balls reserved for later.
- 3. Attach Crossbar to J-box.
- 4. Following all Local Codes and Procedures, make connection from Fixture Lead wires to Supply wires.
- 5. Slide Canopy over bolts on Crossbar and secure Canopy & Light Cluster using reserved Brass Balls.
- 6. To install Frame, remove the bottom Diffuser (Acrylic) Panels.
- 7. Approximately centering the Frame with Canopy, attach Frame with Hanger bolts (included) and secure with hex nut & acorn nut (included) on to ceiling.
- 8. Install 6 Medium Base 60 Watts. (Max.) bulbs (not included) in the socekts.
- 9. Carefully install bottom Disffuser on to the Frame.

