INSTALLATION INSTRUCTIONS

FOR ITEM 163008 Fleur-de-lis Flushmount



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- 1. CANOPY ASSEMBLY
- 2. SHADE RING
- 3. GLASS SHADE

Caution:

Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box.

Be sure power is off at the main breaker box prior to installation.

Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is accounted for.
- 2. Remove perimeter Hex and Acorn Nuts from Canopy Assembly to release Mounting Plate. Reserve Nuts.
- 3. Affix Mounting Plate to ceiling ensuring that connection is suitable to hold a minimum of 80lbs and that Electrical Supply Wires remain accessible at center of Plate.
- 4. Remove Hex and Acorn Nuts from Wire Access panel to release Light Cluster. Reserve Nuts.
- 5. Lift Canopy up to ceiling allowing Mounting Plate Studs to pass through perimeter holes. Secure with reserved Nuts.
- 6. Following All Local Codes and Procedures, make connection from Fixture Lead Wires to Supply Wires.
- 7. Slide Wire Access Panel onto Studs and secure with reserved Nuts.
- 8. Install 8-E26 60Watt Bulbs(not included) into Sockets.
- 9. Set Glass Shade into Shade Ring and hang by connecting Shade Ring to Canopy using Quick Links.
- 10. Power on and ENJOY!!!

