

INSTALLATION INSTRUCTIONS

FOR ITEM 170883 CILINDRO SEMI-FLUSHMOUNT

Meyda
CUSTOM LIGHTING

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

Caution:

***Be sure power is off at the main breaker box prior to installation.
Read all instructions in their entirety before beginning installation.***

1. Carefully unpack all components and make certain that everything is accounted for.
2. Unscrew Ball Finial from Canopy to release Crossbar with Threaded Nipple.
3. Affix Crossbar with Nipple to Junction Box ensuring the connection is suitable to hold a minimum of 20lbs and that Electrical Supply Wires remain accessible.
4. Following All Local Codes and Procedures make Electrical Connection from Fixture Lead Wires to Supply Wires.
5. Lift Fixture up to ceiling allowing Threaded Nipple to pass through Canopy. Secure with Ball Finial.
6. Install 4-E26 40Watt Bulbs(not included) into Sockets.
7. Power on and ENJOY!!!

