

INSTALLATION INSTRUCTIONS

FOR ITEM 174745



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

Fixture Components

1. FRAME W/ACRYLIC BOWL
2. CROSSBAR W/STUDS
3. CANOPY W/LIGHT CLUSTER

Caution:

Be sure power is off at the main breaker box prior to installation.

Read all instructions in their entirety before beginning installation.

1. Carefully unpack all components and make certain that everything is on hand.
2. Release Crossbar from Canopy by unscrewing the two Ball nuts on the canopy, keep for later.
3. Using customer supplied hardware, affix Crossbar directly to J-box ensuring the connection is suitable for a minimum of 20LBS & that electrical supply wires remain accessible.
4. Unscrew the screws on the Frame to release the Frame from the Light Cluster, keep them for later.
5. Following all local codes and procedures, make electrical connection from supply wires to fixture lead wires.
6. Carefully insert Canopy back into studs from Crossbar and secure with previous ball nuts from canopy.
7. Install 2 x E12 BA10 40 Watts Bulbs (not included) into socket.
8. Lift the frame up with Acrylic Bowl and secure with screws from previous.
9. Power on and ENJOY!!

