INSTALLATION INSTRUCTIONS

FOR ITEM 174907 REVIVAL DECO CILINDRO FLUSHMOUNT



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL **INJURY OR DEATH AND PROPERTY DAMAGE.** We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.* **Caution**: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- 1. CEILING HARDWARE
- 2. SHADE

Caution:

Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box. Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is accounted for.
- 2. Remove Hex and Acorn Nuts from Ceiling Hardware to release Mounting Plate. Reserve Nuts for later use.
- 3. Using Customer Supplied 1/4" Hardware, affix Mounting Plate to ceiling ensuring the connection is suitable to hold a minimum of 100lbs and that Electrical Supply Wires remain accessible.
- 4. Following all Local Codes and Procedures, make electrical connection from Fixture Lead Wires to Supply Wires.
- 5. Lift Ceiling Hardware up to ceiling allowing Mounting Plate Studs to pass through Hardware Body. Secure with reserved Hex and Acorn Nuts.
- 6. Install 8 GU24 Base 12Watt LED or 26Watt CFL Bulbs(not included) into Sockets.
- 7. Lift Shade up to Ceiling Hardware ensuring to align Cutouts in top of Shade Frame with Hardware Arms. Once Hardware Arms engage Shade Frame, twist Shade Counter-clockwise until it stops and release.
- 8. Power on and ENJOY!!!

