INSTALLATION INSTRUCTIONS

FOR ITEM 178384 (7"Sq Elk at Dawn Mini Pendant)



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL

INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- 1. CANOPY ASSEMBLY (CANOPY, CROSSBAR W/ STUDS)
- PENDANT

Caution:

Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box.

Be sure power is off at the main breaker box prior to installation.

Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is on hand.
- 2. Release Ćrossbar from Canopy Assembly by unscrewing the Brass Balls, reserve for later use.
- 3. Using Customer Supplied hardware, affix Crossbar directly to J-box ensuring that connection is suitable for a minimum of 15 lbs. and that electrical supply wires remain accessible.
- 4. Weave the Lead Wires through every 3rd link of the Chain.
- 5. Following all local codes and procedures, make electrical connections from Supply Wires to Pendant Lead Wires.
- 6. Lift Canopy up to the ceiling, protruding stud through canopy.
- 7. Resecure Canopy with the Brass Balls from before.
- 8. Install 1X 60W E26 A19 Bulb (not included) into the Socket.
- 9. Power On and Enjoy!!!



