

INSTALLATION INSTRUCTIONS

FOR ITEM 190675 GINA 24 LIGHT CHANDELIER

Meyda
CUSTOM LIGHTING

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

1. CANOPY ASSEMBLY
2. 180" CHAIN
3. HUB W/4 WIRED ARMS
4. 8 LIGHT TOP TIER W/2 WIRED ARMS
5. 16 LIGHT BOTTOM TIER
6. ARM (QTY 10)
7. CANDLE COVERS (QTY 24)

Caution:

Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box. Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

1. Carefully unpack all components and make certain that everything is accounted for.
2. Remove Acorn Nuts from Canopy Assembly to release Mounting Plate. Reserve Nuts for later use.
3. Affix Mounting Plate to ceiling ensuring that connection is suitable to hold a minimum of 225lbs and that Electrical Supply Wires remain accessible.
4. Attach desired length of Chain to Quick Link on Hub.
5. Weave Fixture Lead Wires and Safety Cable through every 5th Link of Chain.
6. Slide Canopy over Chain, Wire, and Cable and let it rest on top of Hub.
7. Hang Hub by connecting loose end of Chain to Quick Link on Mounting Plate Loop.
8. Attach Safety Cable to secure location in ceiling ensuring that connection is suitable to hold a minimum of 225lbs.
9. Following all Local Codes and Procedures, make connection from Fixture Lead Wires to Supply Wires.
10. Slide Canopy up Chain to ceiling allowing Mounting Plate Studs to protrude through. Secure with Reserved Acorn Nuts.
11. Hang 8 Light Top Tier from Hub ensuring to align Wired Arms with Wire Receptacles on Tier Loops. Attach Arms, with open ends facing out, to Top Tier Loops. Lift Top Tier and hang from Hub Loops. Wired Arms may need to be removed from Hub Loops just enough to attach Arms to Tier Loops and then reattach to Hub.
12. Make 4 connections from Arm Wires to Loop-Wire Receptacles.
13. Hang 16 Light Bottom Tier from Top Tier ensuring to align Wired Arms with Wire Receptacles on Tier Loops. Attach Arms, with open ends facing out, to Bottom Tier Loops. Lift Bottom Tier and hang from Top Tier Loops. Wired Arms may need to be removed from Top Tier Loops just enough to attach Arms to Bottom Tier Loops and then reattach to Top.
14. Make 2 connections from Arm Wires to Loop-Wire Receptacles.
15. Slide Candle Covers onto Sockets.
16. Install 24 Candelabra Base 60Watt Bulbs(not included) into Sockets.
17. Power on and ENJOY!!!

