INSTALLATION INSTRUCTIONS

FOR ITEM 193395 CILINDRO FLUSHMOUNT



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- A. 72"W FLUSHMOUNT BODY
- B. 35.5"W IDALIGHT DIFFUSER
- C. SUPPORT ROD (QTY 3)
- D. MOUTING PLATE
- E. THREADED ROD W/FINIAL

Caution: Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is accounted for.
- 2. Affix Mounting Plate to structure assuring that the connection is suitable for minimum 110lbs and that Electrical Supply Wires remain accessible.
- 3. Remove Hex Nut from bottom of Support Rods and screw Threaded Rod into Couplers on top of Flushmount Body Spider.
- 4. Measure distance from center of Flushmount Body to Support Rods. Use measurements for Support Rod placement in ceiling.
- 5. Make electrical connection from Structure Supply Wires to Fixture Lead Wires following all Local Codes and Procedures.
- 6. Hang Fixture by sliding Canopy over Studs on Mounting Plate. Secure using Hex and Acorn Nuts.
- 7. Anchor Support Rods inside ceiling to Structure.
- 8. Install 12 Medium Base 40Watt Bulbs(not included).
- 9. Screw Threaded Rod w/ Finial into Coupler at bottom of Light Cluster.
- 10. Remove Finial and Slide Idalight Diffuser onto Threaded Rod and butted up to Knurled Nut. Replace Finial.
- 11. Power on and ENJOY!!!



