## INSTALLATION INSTRUCTIONS

FOR ITEM 193673 SONOMA SEMI FLUSHMOUNT



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.\*

**Caution**: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

## FIXTURE COMPONENTS

- 1. CANOPY ASSEMBLY AND LIGHT CLUSTER
- 2. ARM (QTY 6)
- 3. SHADE

## Caution:

## Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is accounted for.
- 2. Remove Brass Balls from Canopy Assembly release Universal Crossbar with Studs. Reserve Balls.
- 3. Affix universal Crossbar to Junction Box ensuring that connection is suitable to hold a minimum of 25lbs and that Electrical Supply Wires remain accessible.
- 4. Following All Local Codes and Procedures, make connection from Fixture Lead Wires to Supply Wires.
- 5. Hang Canopy and Light Cluster by sliding Canopy onto Crossbar Studs. Secure with Brass Balls.
- 6. Hang Arms from Canopy Loops.
- 7. Hang Shade by connecting loose ends of Arms to Shade Loops.
- 8. Install 6-E26 60Watt Bulbs(not included) into Sockets.
- 9. Power on and ENJOY!!!

