INSTALLATION INSTRUCTIONS

FOR ITEM 193968 CERO 8LT ISLAND PENDANT



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- 1. FIXTURE HARDWARE
- 2. CANOPY ASSEMBLY
- 3. 2" DIAMETER RING (QTY 2)
- 4. AMBER QUARTZ IDALIGHT CYLINDERS (QTY 8)

Caution: Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is accounted for.
- 2. Unscrew Acorn Nuts from Canopy Assembly to release Mounting Plate.
- 3. Attach Mounting Plate to ceiling ensuring that connection is suitable for minimum 30lbs and that Electrical Line Wires remain accessible.

J-Box does not need to be centered on Canopy Assembly. Ample Fixture Lead Wires are provided to allow for electrical connection anywhere within the 34"L of Canopy Assembly.

- 4. Open Quick Links attached to Loops on Canopy Cover Plate and Attach 2" Diameter Rings. Close Quick Links.
- 5. Unravel Fixture Lead Wires from top of Fixture Hardware and run through Loops on Canopy Cover Plate.
- 6. Make electrical connection from Fixture Lead Wires to Structure Line Wires following all Local Codes and Procedures.
- 7. Slide Canopy Cover Plate over Studs on Mounting Plate and secure with Acorn Nuts. Nuts should be tightened until top of Canopy Cover Plate is flush with ceiling.
- 8. Hang Fixture Hardware from 2" Diameter Rings and feed excess Electrical Wire into Canopy Assembly.
- 9. Install 8 Candelabra Base 40Watt Bulbs(not included) into Sockets.
- 10. Place Idalight Cylinders into Fixture Hardware.
- 11. Power on and ENJOY!!

