

# INSTALLATION INSTRUCTIONS

FOR ITEM 196223 WHISPERING PINES CHANDEL-AIR

*Meyda*  
CUSTOM LIGHTING

**CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE.** We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.\*

**Caution:** Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

## FIXTURE COMPONENTS

1. CANOPY ASSEMBLY
2. DOWN ROD
3. 55"W CHANDEL-AIR BODY
4. SPLIT COLLAR W/CHAINS

### Caution:

**Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box. Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.**

1. Carefully unpack all components and make certain that everything is accounted for.
2. Affix Fixture Mounting Plate with Saddle to structure ensuring that connection is suitable for minimum of 120lbs and that Electrical Supply Wires remain accessible.
3. Unravel Fixture Lead Wires and Safety Cable from top of Chandel-Air Body and feed through Down Rod.
4. Attach Down Rod Flange to top of Chandel-Air Body and secure with Hex and Acorn Nuts.
5. Slide Canopy over Down Rod and allow to rest on top of Chandel-Air Body.
6. Slide Half Steel Ball over Down Rod. Insert Spring Pin through channel at top of Down Rod. Hold Half Steel Ball to allow Spring Pin to seat inside. Bend Pegs from Half Ball over Spring Pin to hold in place.
7. Lift Fixture up to Mounting Plate and seat Half Steel Ball in Mounting Plate Saddle.
8. Make electrical connection from Fixture Lead Wires to Structure Supply Wires following all Local Codes and Procedures.
9. Secure Fixture Safety Cable to structure ensuring that connection is suitable for minimum 120lbs.
10. Slide Canopy up Down Rod and secure to Mounting Plate Studs using Acorn Nuts.
11. Install 10 Medium Base 60Watt Bulbs(not included) into interior Sockets and 10 Medium Base 50Watt MR16 Bulbs(not included) into Up and Down Light Sockets.
12. Attach loose ends of Stay Chains to loops on Chandel-Air Body using Quick Links.
13. Remove Split Collar Bolts to separate Collar and wrap around Down Rod. Placement of Split Collar on Down Rod should be determined by allowing Stay Chains to drape with a gentle curve. Tighten Split Collar Bolts to secure position.
14. Power on and ENJOY!!!

