

# INSTALLATION INSTRUCTIONS

FOR ITEM 197376

*Meyda*  
CUSTOM LIGHTING

**CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE.** We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.\*

**Caution:** Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

## **Caution:**

***Be sure power is off at the main breaker box prior to installation.  
Read all instructions in their entirety before beginning installation.***

1. Carefully unpack all components and make certain that everything is accounted for.
2. Remove Brass Balls from Canopy to release Crossbar with Studs. Reserve Brass Balls for later use.
3. Affix Crossbar to Junction Box using Customer Supplied Hardware ensuring that connection is suitable to hold a minimum of 10lbs and that Electrical Supply Wires remain accessible.
4. Following all Local Codes and Procedures, make electrical connection from Fixture Lead Wires to Supply Wires.

***FIXTURE INCLUDES CANOPY SWIVELS TO LEVEL WHEN HUNG FROM SLOPED CEILING.***

***ENSURE SLOTS IN SWIVELS FACE CEILING SLOPE, PERPENDICULAR TO JOIST.***

***IF NECESSARY, LOOSEN HEX NUTS ON TOP OF CANOPY TO ADJUST SWIVEL SLOT POSITION.  
RE-TIGHTEN ONCE ADJUSTED.***

5. Lift Fixture up to ceiling allowing Crossbar Studs to pass through Canopy. Secure with reserved Brass Balls.

6. Install 2 Medium Base PAR30 13Watt LED Bulbs(not included) into Sockets.

7. Power on and ENJOY!!!

