INSTALLATION INSTRUCTIONS

FOR ITEM 19808 FLEUR DE LIS INVERTED PENDANT



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- 1. CANOPY ASSEMBLY
- 2. 36" CHAIN
- 3. HUB W/LEAD WIRE

- 4. ARM (QTY 8)
- 5. SHADE & SHADE RING
- 6. LIGHT BAR

Caution:

Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is accounted for.
- 2. Unscrew Collar from from Canopy Assembly to release Crossbar with Loop & Quick Link.
- 3. Mount Crossbar to J-Box ensuring that connection is suitable to hold a minimum of 40lbs and that Electrical Supply Wires remain accessible.
- 4. Unravel Fixture Lead Wire from top of Hub and attach desired length of Chain to Quick Link.
- 5. Weave Fixture Lead Wire through Chain.
- 6. Slide Screw Collar and Canopy over Wire & Chain and allow them to rest on top of Hub.
- 7. Hang Hub by attaching loose end of Chain to Quick Link on Crossbar Loop.
- 8. Feed Fixture Lead Wires through Channel in Crossbar Loop and, following all Local Codes and Procedures, make connection to Electrical Supply Wires.
- 9. Slide Canopy up to ceiling and secure by threading Screw Collar onto Crossbar Loop.
- 10. Hang Arms from Hooks on Hub.
- 11. Set Shade into Shade Ring and lift them up and hang them from Arms.
- 12. Set Light Bar into Shade Ring aligning Wire on Bar with Wire from Arm.
- 13. Secure Light Bar with Hex Nuts and make Wire connection.
- 14. Install 4 Medium Base 60Watt Bulbs(not included).
- 15. Power on and ENJOY!!!

