

INSTALLATION INSTRUCTIONS

FOR ITEM 202794 NOZIROH 46 LIGHT TWO TIER CHANDELIER

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

1. ALADDIN LIFT COMPATIBLE CANOPY ASSEMBLY
2. 180" CHAIN
3. HUB WITH ATTACHED LEAD WIRES, SAFETY CABLE, AND WIRED 60" ARM
4. 60" ARM (QTY 2)
5. 84" WIDE TOP TIER WITH ATTACHED WIRED 15" ARM
6. 15" ARM (QTY 2)
7. 49" WIDE BOTTOM TIER
8. ACRYLIC CYLINDER SHADES (QTY 46)

Caution:

Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box.
Be sure power is off at the main breaker box prior to installation.
Read all instructions in their entirety before beginning installation.

1. Carefully unpack all components and make certain that everything is accounted for.
2. Remove Screw Collar from Canopy Assembly to release 1/2" Running Thread with Loop. Reserve Screw Collar for later use.
3. Attach Running Thread with Loop to Aladdin Lift Coupling following Lift's recommended procedure.
4. Attach Chain to Loop on Hub using Quick Link.
5. Weave Fixture Lead Wires and Safety Cable through every 3rd Link of Chain.
6. Slide Screw Collar and Canopy over loose end of Chain and feed Safety Cable through outer hole in Canopy.
7. Hang Hub by connecting loose end of Chain to Running Thread Loop using Quick Link.
8. Secure Safety Cable per Local Codes and Lift specifications.
9. Secure Canopy to Running Thread and Loop using Screw Collar.
10. Feed Lead Wires through Loop Channel and make electrical connection from Fixture Lead Wires to Supply Wires following all Local Codes and Procedures..
11. Hook 60" Arms on available Hub Loops.
12. Hang 84" Wide Top Tier from Arms ensuring to align Wired Arm with Electrical Connectors located at Tier Loop.
13. Make connections from Arm Wires to Tier Wires. Either Arm Wire can connect to either Tier Wire.
14. Hook 15" Arms on available Top Tier Loops.
15. Hang 49" Wide Bottom Tier from Arms ensuring to align Wired Arm with Electrical Connector located at Tier Loop.
16. Make connection from Arm Wire to Tier Wire.
17. Install 46 Candelabra Base 25 Watt Bulbs(not included) into Sockets.
18. Set Acrylic Shades into Shade Cups.
19. Power on and ENJOY!!!

