

INSTALLATION INSTRUCTIONS

FOR ITEM 211565 BARBURY 24 LIGHT CHANDELIER

Meyda
CUSTOM LIGHTING

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

1. CANOPY ASSEMBLY
2. 30" CHAIN
3. HUB W/ 2 ATTACHED WIRED ARMS
4. ARM (QTY 2)
5. LIGHT RING
6. ANTI-SWAY WALL MOUNT HARDWARE
7. ANTI-SWAY CHAIN (QTY 4)

Caution:

Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box. Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

1. Carefully unpack all components and make certain that everything is accounted for.
2. Unscrew Collar from Canopy Assembly to release Mounting Plate with Loop.
3. Affix Mounting Plate to ceiling ensuring that connection is suitable to hold a minimum of 120lbs. and that electrical supply wires remain accessible.
4. Attach desired length of Chain to Hub.
5. Weave Fixture Lead Wires and Safety Cable through every 5th Link of Chain.
6. Feed Fixture Lead Wire through satellite hole in Canopy. Feed Chain and Safety Cable through Screw Collar and central hole in Canopy.
7. Hang Hub by connecting loose end of Chain to Mounting Plate Loop.
8. Feed Safety Cable through Mounting Plate Loop Channel and secure to structure ensuring that connection is suitable to hold a minimum of 120lbs.
9. Following all Local Codes and Procedures, make electrical connection from Fixture Lead Wires to Supply Wires.
10. Slide Canopy up to ceiling and secure by screwing Collar onto Mounting Plate Loop.
11. Hang Arms from Loops on Hub.
12. Hang Light Ring from Arms ensuring to align Wired Arms with Electrical Receptacles on Light Ring.
13. Make connection from Plugs on Wired Arms to Receptacles on Light Ring.
14. Affix Anti-Sway Wall Mount Hardware to desired locations.
15. Attach Anti-Sway Chains to Loops on Light Ring and run Chains to Wall Mount Hardware and connect.
16. Install 24 Medium Base 40Watt Bulbs(not included) into Sockets.
17. Power on and ENJOY!!!

