

INSTALLATION INSTRUCTIONS

FOR ITEM 216339 MADISON SEMI-FLUSHMOUNT

Meyda
CUSTOM LIGHTING

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

1. CANOPY, STEM, & LIGHT CLUSTER
2. ARM (QTY 8)
3. ACRYLIC BOWL
4. THREADED ROD AND FINIAL ASSEMBLY

Caution:

***Be sure power is off at the main breaker box prior to installation.
Read all instructions in their entirety before beginning installation.***

1. Carefully unpack all components and make certain that everything is accounted for.
2. Unscrew Brass Balls from Canopy to release Crossbar with Studs. Reserve Balls for later use.
3. Affix Crossbar to J-Box using Customer Supplied Hardware ensuring that electrical supply wires remain accessible.
4. Screw Stem into Light Cluster until tight.
5. Following all Local Codes and Procedures, make electrical connection from Fixture Lead Wires to structure Supply Wires.
6. Lift Canopy, Stem, & Light Cluster up to ceiling allowing Crossbar Studs to protrude through Canopy. Secure with reserved Brass Balls.
7. Attach Loops on Arms to Loops on Acrylic Bowl using Quick Links.
8. Lift Bowl up to Hanging Hardware and hook loose ends of Arms to Loops on Canopy.
9. Screw Threaded Rod into Coupler on bottom of Light Cluster.
10. Slide Finial Cap over Threaded Rod at bottom of Bowl and secure with Ball Finial.
11. Install 12 Medium Base 40Watt Bulbs(not included) into Sockets.
12. Power on and ENJOY!!!

