## INSTALLATION INSTRUCTIONS

FOR ITEM 216717 CILINDRO ASHCROFT 30 LIGHT CHANDLIER



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.\*

**Caution**: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

## FIXTURE COMPONENTS

- 1. CANOPY ASSEMBLY
- 2. 55" CHAIN
- 3. CHANDELIER BODY
- 4. CRACKLE GLASS SHADE (QTY 30)

## Caution:

## Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box. Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is accounted for.
- 2. Unscrew Knobs from Canopy Assembly to release Mounting Plate. Reserve Knobs for later use.
- 3. Affix Mounting Plate to ceiling ensuring that connection is suitable to hold a minimum of 80lbs and that Electrical Supply Wires remain accessible.
- 4. Attach desired length of Chain to Loop on Chandelier Body.
- 5. Weave Lead Wires and Safety Cable through every 4th Link of Chain.
- 6. Feed Lead Wires and Safety Cable through Canopy Loop Channel and attach loose end of Chain to Canopy Loop.
- 7. Attach Safety Cable to secure location in ceiling ensuring that connection is suitable to hold a minimum of 80lbs.
- 8. Following all Local Codes and Procedures make electrical connection from Lead Wires to Supply Wires.
- 9. Lift assembled Fixture up to ceiling allowing Mounting Plate Studs to pass through Canopy. Secure with reserved Knobs.
- 10. Install 30 Candelabra Base 40Watt Bulbs(not included) into Sockets.
- 11. Set Glass Shades, threaded side down, into Cups and twist Clockwise only far enough for threads to engage. DO NOT OVER TIGHTEN. Care should be taken to ensure threads are not crossed. Cease twisting if any resistance is felt and begin this step again.

12. Power on and ENJOY!!!

