

# INSTALLATION INSTRUCTIONS

FOR ITEM 218160 CITADEL 4 LIGHT PENDANT

*Meyda*  
CUSTOM LIGHTING

**CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE.** We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.\*

**Caution:** Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

## FIXTURE COMPONENTS

1. CANOPY ASSEMBLY
2. 144" CHAIN
3. PENDANT BODY
4. 8.5"W x 17.75"W GLASS PANEL (QTY 4)
5. 4"W x 16"H GLASS PANEL (QTY 4)
6. CANDLE COVER (QTY 4)

### Caution:

**Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box. Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.**

1. Carefully unpack all components and make certain that everything is accounted for.
2. Unscrew Collar from from Canopy Assembly to release Crossbar, Brass Loop, & Quick Link.
3. Mount Crossbar to secure location ensuring that connection is suitable to hold a minimum of 40lbs and that Electrical Supply Wires remain accessible.
4. Unscrew Acorn Nuts from inside corners of Pendant Body to release Angled Corner Plates. Reserve all for later use.
5. Install Glass Panels by gently setting them into Pendant Body interior. Glass Panels can be temporarily held in place using painters tape.
6. Once 2 adjacent Panels have been moved into position, they can be secured using reserved Angled Corner Plates and Acorn Nuts. Repeat until all Panels have been installed and secured.
7. Unravel Fixture Lead Wire from top of Pendant Body and attach desired length of Chain to Quick Link.
8. Weave Fixture Lead Wire through every 5th Link of Chain.
9. Slide first Screw Collar and then Canopy over Chain and let them rest on top of Pendant Body.
10. Hang Fixture Body by attaching loose end of Chain to Quick Link on Crossbar Loop.
11. Feed Fixture Lead Wire through channel in Crossbar Loop and make electrical connection to Structure Supply Wires following all Local Codes and Procedures.
12. Slide Canopy and Screw Collar up Chain and thread Screw Collar onto Brass Loop until top of Canopy is flush with ceiling.
13. Slide Candle Covers over Sockets.
14. Install 4 Candelabra Base 60Watt Bulbs(not included) into Sockets.
15. Power on and ENJOY!!!

