

INSTALLATION INSTRUCTIONS

FOR ITEM 224138 GRACE 10 LT TWO TIER CHANDELIER

Meyda
CUSTOM LIGHTING

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

1. CANOPY ASSEMBLY
2. 72" CHAIN
3. CHANDELIER BODY
4. CANDLE COVER (QTY 9)
5. FABRIC SHADE (QTY 9)

Caution:

**Be sure power is off at the main breaker box prior to installation.
Read all instructions in their entirety before beginning installation.**

1. Carefully unpack all components and make certain that everything is accounted for.
2. Remove Screw Collar from Canopy Assembly to release Crossbar with attached Loop and Quick Link.
3. Affix Crossbar to Junction Box using Customer Supplied Hardware. Ensure that connection is suitable to hold a minimum of 25lbs and that Electrical Supply Wires remain accessible.
4. Unravel Fixture Lead Wires and Safety Cable from top of Chandelier Body and connect desired length of Chain to Quick Link.
5. Weave Lead Wires and Safety Cable through every 5th Link of Chain.
6. Feed Chain and Safety Cable through Screw Collar and center hole in Canopy.
7. Feed Lead Wires through satellite hole in Canopy.
8. Hang Fixture by attaching loose end of Chain to Quick Link on Crossbar Loop.
9. Feed Safety Cable through Channel in Crossbar Loop and connect to secure location ensuring that connection is suitable to hold a minimum of 25lbs.
10. Following all Local Codes and Procedures, make electrical connections from Fixture Lead Wires to Supply Wires. Chandelier Arm Lights and Downlight have separate Lead Wires. Lead Wires are labeled. If desired, Arm Lights and Downlight can be connected to separate Supply Wires and Switches to be controlled independently of each other.
11. Slide Canopy up to ceiling and secure by threading Collar onto Crossbar Loop.
12. Place Candle Covers onto Sockets.
13. Install 9 Candelabra 40Watt Bulbs(not included) into Sockets.
14. Spread Spring Clips inside Fabric Shades and clip them onto Candelabra Bulbs.
15. Install 1 Medium Base 50Watt MR16 Bulb(not included) into Downlight Socket.
16. Power on and ENJOY!!!

