

INSTALLATION INSTRUCTIONS

FOR ITEM 227086 ELEPHANT INVERTED PENDANT

Meyda
CUSTOM LIGHTING

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- | | |
|---|-------------------------------|
| 1. CANOPY ASSEMBLY | 5. SHADE |
| 2. 120" CHAIN | 6. TOP DIFFUSER PANEL (QTY 4) |
| 3. HUB, STEM, SHADE CROSSBAR, LIGHT CLUSTER | 7. DIFFUSER HARDWARE |
| 4. ARM (QTY 3) | |

Caution:

Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box. Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

1. Carefully unpack all components and make certain that everything is accounted for.
2. Remove Screw Collar from Canopy Assembly to release Mounting Crossbar with attached Loop.
3. Affix Mounting Crossbar to ceiling ensuring that connection is suitable to hold a minimum of 120lbs and that Electrical Supply Wires remain accessible.
4. Lower Light Cluster into Shade allowing Shade Crossbar to set beneath Shade Rim. Align holes at ends of Crossbar with holes in Shade Rim and secure with provided Button Head Cap Screws.
5. Thread Stem into Coupling at center of Shade Crossbar.
6. Attach desired length of Chain to Quick Link on Hub Loop.
7. Weave Lead Wires and Safety Cable through every 4th Link of Chain.
8. Slide Screw Collar and Canopy over Cable, Wire, and Chain and allow them to rest on top of Hub.
9. Hang Fixture by attaching loose end of Chain to Quick Link on Mounting Crossbar Loop. While lifting Fixture, Arms should be attached from Hub to Shade for stabilization and support.
10. Slide Canopy and Screw Collar up Chain and feed Safety Cable through satellite hole in Canopy.
11. Attach Safety Cable to secure location in ceiling ensuring that connection is suitable to hold a minimum of 120lbs.
12. Feed Lead Wires through Channel in Mounting Crossbar Loop.
13. Following all Local Codes and Procedures, make electrical connection from Fixture Lead Wires to Supply Wires.
14. Lift Canopy up to ceiling and secure by threading Screw Collar onto Mounting Crossbar Loop.
15. Install 12 Medium Base 60Watt Bulbs(not included) into Sockets.
16. Set Top Diffuser Panels onto Shade and secure with provided Washers and Acorn Nuts on Shade Crossbar Studs.
17. Power on and ENJOY!!!

