INSTALLATION INSTRUCTIONS

FOR ITEM 227743 COSTELLO 18 LIGHT TWO TIER CHANDEL-AIR



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- 1. CANOPY ASSEMBLY
- 2. STEM W/UPLIGHT ASSEMBLY
- 3. UPPER ARM (QTY 5)
- 4. UPPER TIER
- 5. MAIN STEM W/ WIRES & WIRED ARM
- 6. LOWER ARM (QTY 6)

- 7. LOWER TIER W/ FAN LEAD AND SAFETY CABLE
- 8. MISC HARDWARE
 - a. BUTTON HEAD, LOCK WASHER, NUT (QTY 23)
 - b. HEX NUT (QTY 8)
 - c. ACORN NUT (QTY 4)
- 9. CANDLE COVER (QTY 18)

Caution:

Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box. Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is accounted for.
- 2. Carefully stack Upper Tier on top of Lower Tier.
- 3. Feed Fan Lead Wire and Safety Cable through Main Stem.
- 4. Matching Wire colors, make wire connections from Main Stem to Lower Tier.
- Black and White to Black and White. Silver to Silver. Brown to Brown. Green to Green.
- 5. Set Main Stem Plate onto Lower Tier allowing Studs to pass through and secure with Hex and Acorn Nuts.
- 6. Tighten Nut that connects Wired Arm to top of Main Stem.
- 7. Lift Upper Tier ensuring to align Wired Arm with Wire Receptacle on Upper Tier. Attach Arm to Upper Tier by feeding Button Head Screw through Arm, then Tab and secure on inside with Lock Washer and Nut. Make wired connection.
- 8. Attach remainder of Upper Arms to Tabs on top of Main Stem and to Upper Tier with provided Button Head Screws, Lock Washers, and Nuts. Ensure tapered ends of Arms attach to Tabs on top and wider ends to Upper Tier.
- 9. Attach Lower Arms to Tabs on bottom of Upper Tier and then to Tabs on Lower Tier using Screws, Washers, and Nuts. Ensure tapered ends of Arms attach to Tabs on Upper Tier and wider ends to Lower Tier.
- 10. Feed Fan Lead Wire and Safety Cable through Stem w/ Uplight Assembly.
- 11. Matching Wire Colors, make wire connections from Main Stem Wires to Light Assembly Wires.
- Black and White to Black and White. Silver to Silver. Green to Green. Green to Green.
- 12. Set Stem w/ Uplight Assembly onto Main Stem allowing Studs to pass through. Secure with Hex Nuts.
- 13. Remove Balls from Canopy Assembly to release Mounting Saddle. Reserve Balls for later use.
- 14. Affix Mounting Saddle to ceiling ensuring that connection is suitable to hold a minimum of 300lbs.
- 15. Feed Lead Wires and Safety Cable through Canopy Cover Plate and then Canopy and then
- Steel Half Ball. Slide them down Stem and allow them to rest on top of Uplight Assembly.
- 16. Insert Roll Pin through Channel at top of Stem.
- 17. Slide Half Ball up Stem and allow Roll Pin to seat in Ditch. Fold Steel Wire over Pin to hold Ball in place.
- 18. Lift assembled Fixture up to ceiling and allow Half Ball to seat in Mounting Saddle.
- 19. Attach Safety Cable to secure location ensuring that connection is suitable to hold a minimum of 300lbs.
- 20. Following all Local Codes and Procedures, make wired connections from Fixture Lead Wires to Supply Wires.
- 21. Slide Canopy and Cover Plate up to ceiling allowing Studs to protrude through and secure with reserved Balls
- 22. Slide Candle Covers onto Sockets.
- 23. Install 18 Candelabra Base 5 Watt LED Bulbs(not included) into Candle Sockets.
- 24. Install 16 Medium Base 5 Watt MR16 LED Bulbs(not included) into Up and Down Light Sockets.
- 25. Power on and ENJOY!!!

Fixture Lighting can be controlled with included Dimmer Switches installed at center of Lower Tier or remotely with Master Dimmer Switch(not included).

INSTALLATION INSTRUCTIONS

FOR ITEM 227743 COSTELLO 18 LIGHT TWO TIER CHANDEL-AIR



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

Caution:

Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box.

Be sure power is off at the main breaker box prior to installation.

Read all instructions in their entirety before beginning installation.

