

INSTALLATION INSTRUCTIONS

FOR ITEM 230638 QUADRATO PENDANT

Meyda
CUSTOM LIGHTING

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

1. CANOPY & UPPER STEM (#2)
2. LOWER STEM (#1)
3. PENDANT BODY
4. GLASS PANEL (QTY 4)
5. STEEL CORNER STRAP (QTY 4)

Caution:

**Be sure power is off at the main breaker box prior to installation.
Read all instructions in their entirety before beginning installation.**

1. Carefully unpack all components and make certain that everything is accounted for.
2. Unscrew Brass Balls from Canopy to release Crossbar with Studs. Reserve Balls for later use.
3. Using Customer Supplied Hardware, affix Crossbar to Junction Box ensuring that the connection is suitable to hold a minimum of 40lbs and that Electrical Supply Wires remain accessible.
4. Carefully lower Glass Panel into the Pendant Body. Holding at a slight angle, lift Panel into Top Channel of Pendant Body, then straighten and lower Panel until settled into Bottom Channel.
5. Follow previous instruction to install remainder of Glass Panels.
6. Secure Glass Panels with Steel Corner Straps. Lower Straps into Pendant Body and, with hole side down, hold a slight angle and insert top of Straps behind Pendant Body Top Corner Tabs, then straighten Straps and lower behind Bottom Tabs.
7. Unravel Wires and Cable from top of Pendant Body and feed them through loop in provided Feeder Wire and secure with tape. Insert Feeder Wire into and through Stem #1 and pull Wires and Cable through.
8. Insert Feeder Wire into Stem #2 and pull Wires and Cable through and out of top of Canopy.
9. Thread Stem #2 into Coupling at top of Stem #1 and Stem #1 into Coupling at top of Pendant Body
10. Attach Safety Cable to secure location in ceiling ensuring that connection is suitable to hold a minimum of 40lbs.
11. Following all Local Codes and Procedures, make electrical connection from Fixture Lead Wires to Supply Wires.
12. Lift assembled Fixture up to ceiling allowing Crossbar Studs to pass through Canopy. Secure with reserved Brass Balls.
13. Install 4 Medium Base 60Watt Bulbs(not included) into Sockets.
14. Power on and ENJOY!!!

