

INSTALLATION INSTRUCTIONS

FOR ITEM 231762 Anillo Halo Pendant

Meyda
CUSTOM LIGHTING

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

1. CANOPY ASSEMBLY
2. LIGHT RING
3. AIRCRAFT CABLES (QTY 3)

Caution:

***Be sure power is off at the main breaker box prior to installation.
Read all instructions in their entirety before beginning installation.***

1. Carefully unpack all components and make certain that everything is accounted for.
 2. Remove Brass Balls from Canopy Assembly to release Crossbar w/Studs.
 3. Affix Crossbar to Junction Box ensuring that connection is suitable to hold a minimum of 30lbs and that Electrical Supply Wires remain accessible.
 4. Following All Local Codes and Procedures, make electrical connection from Supply Wires to Driver Input Wires.
 5. If Fixture Dimming is desired, make connection from compatible 0-10V Dimmer Switch(not included) to Dimmer Wires on Driver.
 6. Slide Canopy onto Crossbar Studs and secure with Brass Balls.
 7. Loosen Nuts on Light Ring Cable Grippers and hang Light Ring by feeding loose ends of Cables into Grippers.
- Ensure to run Cable from Canopy Gripper marked as (+) to Light Ring Gripper marked as (+).
Ensure to run Cable from Light Canopy marked as (-) to Light Ring Gripper marked as (-).
8. Set hanging height and level Light Ring by adjusting Cables through Grippers at Light Ring.
 9. Once desired Ring configuration has been achieved, tighten Gripper Nuts at Light Ring and cut excess Cable.
 10. Power on and ENJOY!!!

