INSTALLATION INSTRUCTIONS

FOR ITEM 23222 TWIGS 8 LIGHT SEMI-FLUSHMOUNT



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL **INJURY OR DEATH AND PROPERTY DAMAGE.** We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

Caution:

Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is accounted for.
- 2. Remove Brass Balls from Canopy to release Crossbar with Studs. Reserve Balls for later use.
- 3. Using Customer Supplied Fasteners, affix Crossbar to Junction Box ensuring that connection is suitable to hold a minimum of 10lbs and that Electrical Supply Wires remain accessible.
- 4. Following all Local Codes and Procedures, make electrical connection from Fixture Lead Wires to Supply Wires.
- 5. Lift Fixture up to ceiling allowing Crossbar Studs to pass through Canopy. Secure with reserved Brass Balls. If necessary, shift Twigs at Base of Canopy to access Studs.
- 6. Install 8 Candelabra Base 40Watt Bulbs(not included) into Sockets.
- 7. Power on and ENJOY!!!

