

INSTALLATION INSTRUCTIONS

FOR ITEM 234174 Elk at Lake Oblong Pendant

Meyda
CUSTOM LIGHTING

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

1. CANOPY ASSEMBLY
2. CHAIN (2x30")
3. SHADE FRAME
4. GLASS PANELS

Caution:

***Be sure power is off at the main breaker box prior to installation.
Read all instructions in their entirety before beginning installation.***

1. Carefully unpack all components and make certain that everything is accounted for.
2. Remove Brass Balls from Canopy Assembly to release Universal Crossbar. Reserve Brass Balls for later use.
3. Affix Universal Crossbar to Junction Box ensuring connection is suitable to hold a minimum of 30lbs and that Electrical Supply Wires remain accessible.
4. Attach desired length of Chain to Loops on Shade Frame.
5. Attach loose ends of Chain to Loops on Canopy.
6. Weave Fixture Lead Wires through every 5th Link of Chain and then feed through Canopy Loop.
7. Following All Local Codes and Procedures make connection from Fixture Lead Wires to Supply Wires.
8. Lift Fixture up to ceiling allowing Crossbar Studs to pass through Canopy. Secure with reserved Brass Balls.
9. Install Glass Panels by sliding Panel into top Shade Frame Channel and then lowering Panel into bottom Shade Frame Channel.
10. Install 6-E26 60Watt Bulbs(not included) into Sockets.
11. Power on and ENJOY!!!

