INSTALLATION INSTRUCTIONS

FOR ITEM 235046 LOXLEY 20 LIGHT CHANDELIER



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- 1. CANOPY ASSEMBLY
- 2. 96" CHAIN
- 3. HUB W/LEAD WIRE, SAFETY CABLE, & CHAINS
- 4. CHANDELIER RING
- 5. AMBER GLASS CYLINDER (QTY 20)

Caution:

Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box. Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is accounted for.
- 2. Unscrew Collar from Canopy Assembly to release Crossbar with Brass Loop and Quick Link.
- 3. Affix Crossbar to ceiling ensuring that connection is suitable to hold a minimum of 100lbs and that Electrical Supply Wires remain accessible.
- 4. Unravel Fixture Lead Wires and Safety Cable from top of Hub and attach desired length of Chain to Quick Link.
- 5. Weave Lead Wires and Safety Cable through every 3rd Link of Chain.
- 6. Slide Screw Collar and then Canopy over Chain, Wires, and Cable and allow them to rest on top of Hub.
- 7. Hang Hub by attaching loose end of Chain to Quick Link on Crossbar Brass Loop.
- 8. Feed Safety Cable through Channel in Brass Loop and connect to secure location ensuring that connection is suitable to hold a minimum of 100lbs.
- 9. Feed Lead Wires through Channel in Brass Loop and, Following all Local Codes and Procedures, make Electrical Connection from Lead Wires to Supply Wires.
- 10. Slide Canopy and Screw Collar up Chain to ceiling and secure Canopy by threading Screw Collar onto Brass Loop until top of Canopy is flush to ceiling.
- 11. Hang Chandelier Ring by connecting loose ends of Chains to loops on Ring. Ensure to align Chains with Wires with Power Plugs on Chandelier Ring. Connect Electrical Wires.
- 12. Install 20 Medium Base 40Watt Bulbs(not included) into Sockets.
- 13. Set Glass Cylinders into Chandelier Ring cups.
- 14. Power on and ENJOY!!!



