

INSTALLATION INSTRUCTIONS

FOR ITEM 236480 LOXLEY 24 LIGHT CHANDELIER

Meyda
CUSTOM LIGHTING

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

1. CANOPY ASSEMBLY
2. 240" CHAIN
3. HUB W/ LEAD WIRE, SAFETY CABLE, & 2 WIRED ARMS
4. ARM (QTY 2)
5. 72" CHANDELIER RING
6. 3" x 6" GLASS SHADE (QTY 24)

Caution:

Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box. Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

1. Carefully unpack all components and make certain that everything is accounted for.
2. Unscrew Collar from Canopy Assembly to release Crossbar with Brass Loop and Quick Link.
3. Affix Crossbar to ceiling ensuring that connection is suitable to hold a minimum of 100lbs and that Electrical Supply Wires remain accessible.
4. Unravel Fixture Lead Wires and Safety Cable from top of Hub and attach desired length of Chain to Quick Link.
5. Weave Lead Wires and Safety Cable through every 3rd Link of Chain.
6. Slide Screw Collar and then Canopy over Chain, Wires, and Cable and allow them to rest on top of Hub.
7. Hang Hub by attaching loose end of Chain to Quick Link on Crossbar Brass Loop.
8. Feed Safety Cable through Channel in Brass Loop and connect to secure location ensuring that connection is suitable to hold a minimum of 100lbs.
9. Slide Canopy and Screw Collar to top of Chain and feed Fixture Lead Wires through satellite hole in Canopy. Following all Local Codes and Procedures make electrical connection from Lead Wires to Supply Wires.
10. Secure Canopy by threading Screw Collar onto Brass Loop until top of Canopy is flush with ceiling.
11. Hook Arms to available Loops on Hub.
12. Hang Chandelier Ring from loose ends of arms ensuring to align arms with Power Cables to Loops on Ring with Power Receptacles.
It may be necessary to turn Loop 90° to get final Arm attached.
13. Make connections from Power Plugs to Receptacles.
14. Install 24 Medium Base 40Watt Bulbs(not included) into Sockets.
15. Place Glass Shades over Bulbs and into Ring cups.
16. Power on and ENJOY!!!

