INSTALLATION INSTRUCTIONS

FOR ITEM 237278 KITZI CILINDRO PENDANT



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- 1.CANOPY ASSMBLY
- 2. CHAIN
- 3. PENDANT BODY

Caution:

Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is accounted for.
- 2. Remove Brass Balls from Canopy Assembly to release Universal Crossbar with Studs. Reserve Brass Balls for later use.
- 3. Affix Crossbar to Junction Box with Customer Supplied Fasteners ensuring that connection is suitable to hold a minimum of 30lbs and that Electrical Supply Wires remain accessible.
- 4. Attach desired length of Chain to Quick Link at top of Pendant Body.
- 5. Attach loose end of Chain to Quick Link on Canopy Loop.
- 6. Weave Fixture Lead Wires through every 3rd Link and feed through Canopy Loop.
- 7. Following all Local Codes and Procedures, make electrical connection from Fixture Lead Wires to Supply Wires.
- 8. Lift Canopy up to ceiling allowing Crossbar Studs to pass through. Secure with reserved Brass Balls.
- 9. Unscrew Finial from bottom of Shade and remove Acrylic Diffuser.
- 10. Install 4 Medium Base 60Watt Bulbs(not included) into Sockets.
- 11. Replace Diffuser and secure with Finial.
- 12. Power on and ENJOY!!!

