INSTALLATION INSTRUCTIONS

FOR ITEM 239900 KAHE FLUSHMOUNT



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- 1. FIXTURE HARDWARE
- 2. ACRYLIC BOWL
- 3. SHADE FRAME

Caution:

Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box. Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is accounted for.
- 2. Remove Nuts from Canopy to release Mounting Plate. Reserve Nuts for later use.
- 3. Affix Mounting Plate to ceiling ensuring that connection is suitable to hold a minimum of 150lbs and that Electrical Supply Wires remain accessible.
- 4. Following all Local Codes and Procedures, make electrical connection from Fixture Lead Wires to Supply Wires.
- 5. Lift Fixture Hardware up to ceiling allowing Mounting Plate Studs to pass through holes in Canopy. Secure using reserved Nuts.
- 6. Install 12 GU24 26Watt LED Bulbs(not included) into Sockets.
- 7. Set Acrylic Bowl into Shade Frame.
- 8. Remove Set Screws from top of Shade Frame and reserve.
- 9. Lift Shade Frame with Bowl up to ceiling ensuring to align Notches in top of Shade Frame with Tabs on Canopy. Rotate Shade Frame to the left until Screw Holes in Shade Frame are within Canopy Tabs.
- 10. Thread reserved Screws into Shade Frame until they create solid contact with Canopy.
- 11. Power on and ENJOY!!!

