

# INSTALLATION INSTRUCTIONS

FOR ITEM 247466 MADISON INVERTED PENDANT

*Meyda*  
CUSTOM LIGHTING

**CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE.** We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.\*

**Caution:** Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

## FIXTURE COMPONENTS

1. FIXTURE HARDWARE
2. BOWL CONNECTION HARDWARE
3. ACRYLIC BOWL
4. THREADED ROD W/ FINIAL

### Caution:

**Be sure power is off at the main breaker box prior to installation.  
Read all instructions in their entirety before beginning installation.**

1. Carefully unpack all components and make certain that everything is accounted for.
2. Remove Brass Balls from Canopy to release Crossbar with Studs. Reserve Balls for later use.
3. Using Customer Supplied Hardware affix Crossbar to Junction Box ensuring that connection is suitable to hold a minimum of 30lbs and that Electrical Supply Wires remain accessible.
4. Following all Local Codes and Procedures, make Electrical Connection from Fixture Lead Wires to Supply Wires.
5. Lift Fixture Hardware up to ceiling allowing Crossbar Studs to pass through Canopy. Secure with reserved Brass Balls.
6. Attach Bowl Connection Hardware to holes in Acrylic Bowl. Separate Half Ball from Cable Gripper and with Gripper on inside of Bowl, feed Threaded end through hole and secure with Half Ball on outside of Bowl.
7. Lift Acrylic Bowl up to Fixture Hardware and hang from Aircraft Cables. Loosen Nuts on top of Grippers and feed Cables through.
8. Level Bowl using Cables and Grippers. To release Cables, depress loosened Gripper Nut and pull Cable. Once Bowl is level, tighten Gripper Nuts.
9. Feed Threaded Rod up through bottom hole in Acrylic Bowl and screw into Coupling at bottom of Light Cluster until Finial is flush with bottom of Bowl. Weight of Bowl should be held by Cables not Finial.
10. Install 9 Medium 60Watt Bulbs(not included) into Sockets.
11. Power on and ENJOY!!!

