

INSTALLATION INSTRUCTIONS

FOR ITEM 250112 ANILLO APOLLONIA PENDANT

Meyda
CUSTOM LIGHTING

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

Caution:

Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box. Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

1. Carefully unpack all components and make certain that everything is accounted for.
2. Remove Hex and Acorn Nuts from Canopy Assembly to release Mounting Plate with Studs. Reserve all Nuts for later use.
3. Affix Mounting Plate to ceiling ensuring that connection is suitable to hold a minimum of 50lbs and that electrical Supply Wires remain accessible.
4. Loosen Cable Grippers on Canopy and feed Aircraft Cables with Stoppers down through Canopy and Gripper.
5. Following all Local Codes and Procedures, make electrical connection from Supply Wires to Driver Input Wires.
6. Fixture is Dimmable with compatible 0-10V Dimmer switch. If dimming is desired connect Dimming Wires from Driver to Wires from Dimmer Switch. Purple Driver Wire will connect to Positive Dimmer Wire and Gray Driver Wire will connect to Negative Dimmer Wire.
7. Lift Canopy up to ceiling allowing Mounting Plate Studs to pass through. Secure with reserved Hex and Acorn Nuts.
8. Make connections from loose ends of Cables to Grippers on Hub ensuring to align Cables (+) to (+) and (-) to (-). Fixture Height can be adjusted by extending or retracting Aircraft Cables at Hub.
DO NOT ADJUST CABLES INTO CANOPY
9. Hang Light Ring by running Cables from Grippers in Ring to Grippers on Hub ensuring to align Cables (+) to (+) and (-) to (-).
DO NOT ADJUST CABLE LENGTHS BETWEEN HUB AND LIGHT RING
10. Once Fixture is hung and adjusted to desired drop from ceiling, excess Cable can be cut.
11. Ensure that Aircraft Cables are not touching each other.
12. Power On and ENJOY!!!

