

INSTALLATION INSTRUCTIONS

FOR ITEM 263422 Anillo Halo Pendant

Meyda
CUSTOM LIGHTING

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

1. CANOPY (QTY 3)
2. DRIVER
3. LIGHT RING
4. AIRCRAFT CABLES (QTY 3)

Caution:

Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box. Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

1. Carefully unpack all components and make certain that everything is accounted for.
2. Following All Local Codes and Procedures, make electrical connection from Supply Wires to Driver Input Wires.
3. Run 24V Output Wires from Driver to Junction Boxes. Positive(+) Output Wire should run to 1 J-Box and Negative(-) Output Wire should run to another.
4. Remove Balls from Canopies to release Universal Crossbars.
5. Connect Universal Crossbars to J-Boxes.
6. Connect Positive Output Wire from Driver to Wire Clip in Canopy marked (+).
7. Connect Negative Output Wire from Driver to Wire Clip in Canopy marked (-).
8. Slide Canopies over Crossbar Studs and secure with Balls.
9. Loosen Nuts on Light Ring Cable Grippers and Feed Aircraft Cables through.
10. Loosen Nuts on Canopy Cable Grippers and hang Light Ring by feeding loose ends of Cables into Grippers.
Ensure to run Cable from Light Ring Gripper marked as (+) to Canopy marked as (+).
Ensure to run Cable from Light Ring Gripper marked as (-) to Canopy marked as (-).
Cable should only be inserted approximately 1" into Canopy. Tighten Gripper Nuts.
11. Set hanging height and level Light Ring by adjusting Cables through Grippers at Light Ring.
12. Once desired Ring configuration has been achieved, tighten Gripper Nuts at Light Ring and cut excess Cable.
13. Power on and ENJOY!!!

INSTALLATION INSTRUCTIONS

FOR ITEM 263422 Anillo Halo Pendant

Meyda
CUSTOM LIGHTING

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

Caution:

Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box. Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

