

# INSTALLATION INSTRUCTIONS

FOR ITEM 270540 IVELA FLUSHMOUNT



**CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE.** We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.\*

**Caution:** Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

## FIXTURE COMPONENTS

1. FIXTURE HARDWARE
2. ACRYLIC TUBE (QTY 120)

### **Caution:**

**Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box. Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.**

1. Carefully unpack all components and make certain that everything is accounted for.
2. Remove Nuts from Fixture Hardware to release Mounting Plate. Reserve Nuts for later use.
3. Affix Mounting Plate to ceiling, ensuring that connection is suitable to hold a minimum of 25lbs and that Electrical Supply Wires remain accessible.
4. Set Fixture Hardware on a flat surface allowing it to rest on Sockets and slide Acrylic Tubes into Tube Slots. Note: Rubber Rings should be set in the same location on all Tubes when installing.
5. Following All Local Codes and Procedures, make Electrical Connection from Lead Wires to Supply Wires.
6. Lift Fixture Hardware up to ceiling allowing Mounting Plate Studs to protrude through. Secure with Nuts.
7. Acrylic Tubes should be gently pulled down to rest on Rubber Rings. Gently Pull/Twist Tubes to adjust.
8. Install 6-E26 40Watt Bulbs(not included) into Sockets.
9. Power on and ENJOY!!!

