INSTALLATION INSTRUCTIONS

FOR ITEM 282533 24" X 66"L CASSIDY



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL

INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- 1. FRAME W/ LIGHT CLUSTERS INSTALLED
- CANOPY ASSEMBLY W/ MOUNTING PLATE
- 4 X CHAIN WITH HOOKS

Caution:

Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box.

Be sure power is off at the main breaker box prior to installation.

Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is on hand.
- 2. Separate the M-plate by removing the Acorn nuts and Hex nuts, keep them for later.
- 3. Using customer supplied hardware, affix M-plate to ceiling ensuring that the connection is suitable to hold a minimun of 140 lbs and that electrical supply wires remain accessible.
- 4. Lift the Canopy up and secure to the M-plate using Hex nuts and Acorn nuts from earlier.
- 5. Unscrew the Knurled knob on the Canopy to remove the Wiring lid to get access to lead wires from fixture and supply wires.
- 6. Following all local codes and procedures, make electrical connection from Fixture lead wires to Supply wires.
- 7. Screw back the wiring access panel using the Knurled knob.
- 8. Hung chains with hooks.
- 9. Unravel wire from the top of the Canopy and feed through chain, weaving between every 4 links and down through the loop until the end of the chain.
- 10. Hung the Frame on the Chains.
- 11. Connect Mollex connector.
- 12. Power on and ENJOY!

