INSTALLATION INSTRUCTIONS

FOR ITEM 284691 Shansky Semi-Flushmount



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- 1. HARDWARE
- 2. ARM (QTY 3)
- 3. SHADE

Caution:

Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is accounted for.
- 2. Remove Knobs from Canopy to release Crossbar with Studs. Reserve Knobs for later use.
- 3. Affix Crossbar to Junction Box ensuring connection is suitable to hold a minimum of 15lbs and that Electrical Supply Wires remain accessible.
- 4. Following All Local Codes and Procedures, make connection from Fixture Lead Wires to Supply Wires.
- 5. Lift Hardware up to ceiling allowing Crossbar Studs to protrude through Canopy. Secure with Reserved Knobs.
- 6. Hang Arms from Hooks on Canopy.
- 7. Remove Threaded Rod from bottom of Light Cluster and hang Shade from Arms.
- 8. Feed Threaded Rod up through Shade and screw into Bottom of Light Cluster.
- 9. Install 4-E26 60Watt Bulbs(not included) into Sockets.
- 10. Power on and ENJOY!!!

