

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL

INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.* **Caution:** Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- 1. SHADE FRAME W/ LIGHT CLUSTER INSTALLED
- 2. CANOPY ASSEMBLY W/ MOUNTING PLATE

Caution: Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is on hand.
- 2. Separate the Crossbar by removing the Brass balls, keep them for later.
- 3. Using customer supplied hardware, affix Crossbar to ceiling ensuring that the connection is suitable to hold a minimun of 25 lbs and that electrical supply wires remain accessible.
- Screw in the Running thread into the coupling attached to the frame, simultaneously pushing the lead wires through the running thread.
- 5. Take the Tube and slide it over the Running thread. Put the Check ring on top of it.
- 6. Take the Canopy over the Running thread and secure all by using Spider-washer and Hex nut provided.
- Following all local codes and procedures, make electrical connection from Fixture lead wires to Supply wires.
- 8. Lift the Shade up and secure to the Crossbar using Brass balls from earlier.
- 9. Install 60WATT E26 A19 Bulbs (not included) into Socket.
- 10. Power on and ENJOY!

