

INSTALLATION INSTRUCTIONS

FOR ITEM 284907

Meyda
CUSTOM LIGHTING

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

1. CROSSBAR
2. CANOPY AND WIRE
3. LAMPING ASSEMBLY
4. ACRYLIC BOTTOM
5. FINIAL

Caution:

***Be sure power is off at the main breaker box prior to installation.
Read all instructions in their entirety before beginning installation.***

1. Carefully unpack all components and make certain that everything is on hand.
2. Unscrew brass balls on the bottom of the Canopy to release the Crossbar.
3. Using Customer supplied hardware, affix the Crossbar directly to the J-box ensuring connection is suitable for a minimum of 15 lbs and that electrical supply wires remain accessible.
4. Unravel the wires at the top of the Canopy.
5. Remove the Acrylic Bottom by unscrewing the finial cap at the bottom of the fixture.
6. Lift the Lamping Assembly up. Following all local codes and procedures, make electrical wire connections from fixture lead wires to supply wires.
7. Secure Lamping Assembly to the Crossbar using the brass balls from earlier.
8. Install 3X 12WATT E26 A19 LED Bulbs (not included) into sockets.
9. Lift the Acrylic up and re-install with the finial from before.
10. Power on and ENJOY!!!

