



## IMPORTANT

**TURN OFF THE POWER AT THE MAIN FUSE OR CIRCUIT BREAKER BOX BEFORE STARTING INSTALLATION**

**CAREFULLY UNPACK AND IDENTIFY ALL PARTS BEFORE ASSEMBLY. BULBS ARE NOT INCLUDED**

1. Attach crossbar to outlet box using screws located in outlet box.
2. Install fixture wires and ground wire up through hole in shade vase cap/crossbar. Pull fixture wire with ground wire up until light fixture nipple seats into vase cap/crossbar. Place shade loop onto fixture wires with ground wire, slide down and screw onto light fixture nipple, tighten to vase cap/crossbar.
3. Screw crossbar nipple into crossbar,
4. Attach chain to shade loop. Place canopy nut than canopy onto chain, attach chain to crossbar nipple, Thread fixture wires with ground wire through chain and through crossbar nipple.
5. Wire as per local electrical code.
6. Slide canopy up to ceiling, screw canopy nut onto crossbar nipple and tighten to canopy.



*"A Commitment to Excellence in Lighting and Service"*

CALL OUR CUSTOMER SERVICE DEPARTMENT AT 1-800-222-4009

MONDAY - FRIDAY 8:00 a.m. - 6:00 p.m. ET

visit us on the web at [www.meyda.com](http://www.meyda.com)

