INSTALLATION INSTRUCTIONS

FOR ITEM 69637



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL

INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- 1. FRAME
- 2. CANDLE COVERS (X6)
- 3. CHAIN
- 4. CANOPY
- 5. CROSSBAR W/STUDS

Caution:

Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is on hand.
- 2. Remove Brass Balls from Canopy Assembly to release Universal crossbar. Reserve them for later.
- 3. Using Customer Supplied Hardware, affix Universal Crossbar to Junction Box ensuring connection is suitable to hold a minimum of 25lbs. and that Electrical Supply Wires remain accessible.
- 4. Carefully lift the fixture up to the ceiling allowing Crossbar Studs to pass through Canopy, secure with reserved Brass Balls.
- 5. Unscrew the Ball finial on Canopy to release the wiring access panel, reserve for later.
- 6. Following All Local Codes and Procedures make connection from Fixture Lead Wires to Supply Wires.
- 7. Push the wires back in canopy and secure the wiring access panel back using reserved ball finial.
- 8. Install 6 X E26 CA10 (25W) (not included) into sockets.
- 9. Place Candle covers carefully over the bulbs.
- CANOPY

 FRAME

 BRASS BALL

 BRASS BALL

 BRASS BALL

 FRAME