INSTALLATION INSTRUCTIONS

FOR ITEM 72212 Fleur-de-lis Flushmount



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

FIXTURE COMPONENTS

- 1. CANOPY ASSEMBLY
- 2. STAINED GLASS SHADE
- 3. SHADE RING


Caution:

Fixture is OVERWEIGHT and not suitable for installation with standard Junction Box.

Be sure power is off at the main breaker box prior to installation.

Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is accounted for.
- 2. Remove Acorn and Hex Nuts from Canopy Assembly to release Mounting Plate. Reserve Nuts for later use.
- 3. Affix Mounting Plate to blocking in the ceiling ensuring that connection is suitable to hold a minimum of 300lbs and that Electrical Supply Wires remain accessible.
- 4. Following all Local Codes and Procedures, make Electrical Connection from Fixture Lead Wires to Supply Wires.
- 5. Lift Canopy up to Mounting Plate allowing Studs to pass through. Secure with reserved Hex and Acorn Nuts.
- 6. Set Shade into Shade Ring and secure with Set Screws. (DETAIL B)
- 7. Install 12 Medium Base 60Watt Bulbs(not included) into Sockets.
- 8. Lift Shade up to ceiling aligning Canopy Arms with Slots in Shade Ring. Engage Arms into Slots and twist Shade to secure.
- 9. Power on and ENJOY!!!



MOUNTING PLATE DETAIL

